

XU linija:	XU032	XU058	XU112	XU225	XU343	XU490	XU686	XU980
Laboratorinės kamerinės krosnys (džiovinimo spintos)								

Techninės charakteristikos:

Temp. valdymas	Kambario temperatūra + 10 °C iki 300 °C								
Maksimali temperatūra:	300 °C								
Temperatūros pasiskirstymas prie 105 °C:	± °C	< 1.2	< 1.2	< 1.2	< 1.5	< 1.2	< 1.2	< 1.2	< 1.2
Temperatūros palaikymas	± °C	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2

Darbinių kamerų matmenys:

Talpa:	dm ³	32	58	112	225	343	490	686	980
Plotis:	mm	300	400	500	500	700	700	700	1000
Gylis:	mm	270	360	450	450	700	700	700	700
Aukštis:	mm	400	400	500	1000	700	1000	1400	1400

Gabaritiniai krosnių matmenys:

Apimtis:	m ³	0.16	0.24	0.36	0.61	0.74	0.97	1.28	1.93
Plotis:	mm	465	565	664	668	840	840	840	1140
Gylis:	mm	510	602	692	710	910	910	910	1015
aukštis:	mm	694	694	794	1294	970	1270	1670	1670

Lentynos iš nerūdijančio plieno:

Komplekte / Maksimum:		2 / 6	2 / 6	2 / 8	2 / 17	2 / 11	2 / 17	2 / 24	2 / 24
Lentynų matmenys:	mm	270*240	370*330	470*420	470*420	670*670	670*670	670*670	970*670
Lentynų apkrova /viso:	kg	30/60	30/60	30/60	30/120	30/120	30/240	30/240	30/240

Papildoma informacija:

Durų kiekis:		1	1	1	1	1	1	1	2
Oro ventiliatoriaus našumas:	m ³ /h	200	200	200	400	500	500	1000	1000
Langas duryse: (opcija)	mm	200*200	200*200	180*350	350*350	350*350	350*550	350*550	180*350
Svoris	kg	35	47	54	120	155	205	235	295

Elektrinė dalis:

Galia:	kW	1,050	2,050	2,050	3,100	4,200	4,200	6,300	6,300
Įtampa:	V	230	230	230	230	230	230	400	400